

# ULTIMATE SUPPORT™

THE STRENGTH OF INNOVATION

## PRO MIC STAND

Road-worthy, compact stands designed for the gigging musician.

Heavy-walled, oversized steel tubing is super strong. Clutch is quick, fast, smooth, and noise-free for easy adjustment. Strong zinc die-cast base securely holds up stand.



STANDARD HEIGHT / WEIGHTED BASE



### PRO HEIGHT & BASES



STANDARD

SHORT



STACKABLE

STANDARD

TRIPOD



Rev. 1 03.16.09 . Hang Tag Item #17200T



## FEATURES OF PRO-ST

**Patented Universal Mic Attachment** - Top threads fit both US- and metric-threaded mic clips and accessories.

**Secure Clutch** - Our clutch is fast, secure, and reliable. It locks up smoother and quicker than any other clutch on the market. Now with dual overmolding for a secure grip.

**Durable Construction** - We use thick steel tubing and rubber foot caps that won't fall off.

**Heavy-duty Finish** - Strong coating resists rust and scratches.

**Sturdy Weighted Base** - If you prefer some weight, select a strong, die-cast weighted base in two stable options: standard or stackable. Stackable base cut-out allows up to six stands to stack in the footprint of one for convenient storage and transport.

**Limited Lifetime Warranty** - This product is constructed of the finest materials and backed by our award-winning customer support. For full details, exclusions, and limitations, as well as information on obtaining warranty service, visit [www.ultimatesupport.com](http://www.ultimatesupport.com).

---

## INSTRUCTIONS FOR SETTING UP THE STAND

1. Screw shaft into weighted base. Weighted bases and shafts are interchangeable.
2. Turn the ergonomic Patented Quarter-Turn Clutch a quarter turn and adjust stand height up or down. Securely retighten clutch.
3. Choose US or metric mic attachment and place mic on stand, then turn MIC-Lock.

*Visit [www.ultimatesupport.com](http://www.ultimatesupport.com) to download a detailed product manual, read full warranty details and to register your warranty.*

## SPECS OF PRO-ST

- Item #17200—black
- Tube diameter 1" (25 mm)
- Height 37.4" - 57.9"  
(950 mm - 1470 mm)